



PRODUCT CODE: F2G

Heavy Duty Matting

For the harshest environments



Flexigrid is a hardwearing matting for heavy industrial areas where a production process can generate dirt, grime and spillages of liquids and metal chips. An extra aggressive slip resistant tread pattern ensures safety underfoot whilst being comfortable to stand on. Able to cope with the heaviest of spillages or harshest of applications.

Environmentally Friendly



Manufactured from recycled factory waste that is in turn 100% recyclable at the end of Flexigrid's use.


MODULES

In addition to 10 & 5 metre length rolls, Flexigrid is also available in 1.8m lengths x 60 or 91cm widths.



ANCILLARIES

Aluminium ramped edging available in joinable lengths.




Product name	Height	Length	Width	Width
Flexigrid	20mm	5m	x 60 cm	x 91 cm
	20mm	10m	x 60 cm	x 91 cm
Ancillaries	Anodised aluminium Edging section, 4.5cm width x 20mm height x 2m length + screws and plugs			
Flexigrid Modules	20mm	1.8m	x 60 cm	x 91 cm

OVERALL HEIGHT 20 mm
WEIGHT 9.8 kg/m²

BLACK

KEY FEATURES



ADDITIONAL BENEFITS

- Chemical, oil and acid resistance
- Contours to uneven floor surfaces
- Undershoe dirt removal for entrance applications
- Available in roll format
- Made from 100% factory recycled material

WHY CHOOSE FLEXIGRID?

AT A GLANCE:

Ideal for extra heavy duty areas

Excellent slip resistance

Open-grid facilitates maximum fluid drainage



Plastic Extruders Limited

Russell Gardens, Wickford, Essex, SS11 8DN England
 Tel: +44 (0)1268 571116 Fax: +44 (0)1268 560027
 e-mail: sales@plastex.co.uk www.plastex.co.uk

